



Product Specifications

Professional Applicators

Product Benefits

Professional quality applicator tools are specially designed for TKO patching products. The applicators have sturdy aluminum handles and a thick, flexible rubber "blade" to help smooth and feather patching material.

Product Features

White high-quality rubber, will not mark surface. Aluminum handles will not rust. Can be used with TKO patching and roofing products. Also can be used with other plastering products and faux finishes.

Sizes

9" Applicator



Dual Corner Applicator



Application

Recommended for:

Use with the complete line of interior and exterior TKO Waterproof Coatings' products on the following surfaces:

Exterior: masonry, concrete, cement block, brick, stucco, slate, tile, wood, foam, fiberglass, asphalt, acrylics, single-ply membranes

Interior: drywall, textured and smooth plaster, specialty finishes, stucco, wood, concrete & cement block

General Application Guidelines

Step 1: Brush or use applicator to apply patching compound to recommended thickness.

Step 2: Use applicator to embed Tuffglass Fabric into patching compound.

Step 3: Apply top coat of patching compound to recommended thickness. Use applicator to smooth and feather edges.

Detailed directions for use can be found on roof coating or patching compound packaging.

Warranty

Information is given in good faith, to be used as a guide only and does not assure product suitability for an intended purpose or application. Product is guaranteed to be free of defect. Warranty is limited to replacement of that portion of product proven to be defective. For complete warranty information, contact manufacturer.